
# Swim 'n' Rinse Compact Deck / Transom Shower

## **NEW** Whale Swim 'n' Rinse Compact Shower with Flexible Rubber Cover (cold only)

Ideal for installation where space is limited on deck and behind the bulkhead



Lightweight handset will not damage the gel coat if dropped on deck



RT3000 Whale Swim 'n' Rinse Compact Shower Rubber cover (cold only)



Save water on board

- one touch trigger
handset to conserve
water during showering



Closed cover

# 1 Year Warranty

# Simply swim and rinse without wasting water

- Press trigger to only use the water you need
- · Crisp and clean chrome and white finish
- Extra long hose allows you to fit in most convenient location on deck
- · Highest quality finish stabilized PVC cover
- Simple installation standard size circular holes to drill
- Standard connections suitable for ¾" BSP threaded connections/ Whale Quick Connect 15mm plumbing

#### **COMPLETE YOUR SYSTEM**

Freshwater system accessories such as water filters, and pipework connections – page 76-77

### YOU MAY ALSO LIKE

Whale Twist® - Deck Shower with integrated temperature and flow controls - page 72

Swim 'n' Rinse- deck shower

- The classic transom Shower - page 75

Watermaster Automatic Pressure Pumps – page 54 Whale faucets and showers – page 68-71



### **Product Information**

Model Specifications

| -  | Swim 'n' Rinse Compact Shower   |
|--|---|
| Product Code                                       | Rubber cover (cold only) RT3000   |
| Troduct Code                                       | 1110000   |
| Description  | White and Chrome with angled holder and one touch trigger handset   |
| Diameter of mounting hole                          | 80mm (3 1/8" )  |
| Hose length  | 2.6m (8.5ft)  |
| Hose Connections                                   | $^{3}/_{8}$ " adaptor x $^{1}/_{2}$ " female adapter  |
| Depth Behind the Surface                           | 130 mm (5 <sup>1</sup> / <sub>10</sub> ")   |
| Weight   | 0.535kg (1.18 lbs)  |
| Materials  | Internal components - Hostaform, stainless steel 304,<br>housing UV stabilized Polypropylene, PVC<br>Cover - UV stabilised PVC, fixings - stainless steel |
| To connect to Whale Quick<br>Connect 15mm Plumbing | WX1583B   |

Note: These specifications are retail items only.

For details of our bulk pack range for boat builders and wholesalers - contact Whale Support.

Maximum cold water pressure 2 bar (30 ps)